



Installation and Accessories Product List

Acoustiblok® is a uniquely formulated material and few adhesives or tapes will maintain a bond to it: AC foil tape, duct tape, most silicone and other adhesives will lose their bond, unfortunately sometimes after the drywall is up jeopardizing the results of your sound treatment installation.

Acoustiblok Acoustical Sound Sealant, Acoustigrip™ tape, and Acoustiputty™ sealant pads have been specifically formulated and tested to work with the Acoustiblok Sound Isolation Material. Our independent acoustical test results have been performed using Acoustiblok sealant products, using other products may affect the sound reduction properties of your Acoustiblok treatment.

ACOUSTIGRIP™ TAPE

Acoustigrip (2" x 180', 2.0 mil thk.) tape is specifically formulated to work with the Acoustiblok Sound Isolation Material and permanently bond to the most demanding surfaces. U.L. recognized and CSA accepted.



NOTE: A.C. foil, duct and other tapes may not remain bonded to Acoustiblok® long term; don't jeopardize the sound reduction results of you installation use only proven Acoustiblok products!

Order Number: AGT60

ACOUSTIBLOK ACOUSTICAL SOUND SEALANT

Sound reduction installations require as airtight of a seal possible. Provides excellent sealing properties and decouples adjacent surfaces, helping to minimize structural sound transmission. Very flexible and maintains its flexibility over time. Specifically formulated to work with the Acoustiblok Sound Isolation Material

Order Number: AC10

10 oz. tube

Order Number: AC29

29oz. Fiber Cartridge

Order Number: AC20


20oz. Sausage Tube



ACOUSTIPUTTY™ ACOUSTICAL SEALANT PAD

Acoustiputty Pads are a quick and easy way to make the back of electrical boxes and other holes or other voids airtight. It is formulated specifically to permanently adhere to Acoustiblok (which few products adhere to).

The pads are non-flammable, UL classified, soft and moldable. Excellent in making the required air tight seal required for reduced sound transmission.



Order Number: PPD7

WAFER HEAD TEK SCREW

Screw to fasten Acoustiblok to metal framing. # 8 x 3/4" wafer head tek screw, self-tapping, (approx. 1000 per box)



Order Number: WHS

GRIP RITE™ TIN CAP DISKS

These sheet metal disks increase the holding power when nailing or stapling to wood studs. The disks are used to distribute the weight of the Acoustiblok to reduce the risk of tearing and the material pulling off the fastener. (approx. 500 disks per box)



Order Number: TC5

ACOUSTIBLOK MATERIAL ROLL DISPENSER

A material handling reel for easy, efficient dispensing and handling of Acoustiblok. The safest and most reliable way to roll out, measure, and cut Acoustiblok, is to place the rolls on a pair of steel jack stands. Includes our custom steel spindle made specifically to work with all roll sizes of Acoustiblok. Capacity up to 2,000 LBS



Order Number: RD350

ACOUSTIWOOL™ -TF0.11 TILE FLOOR UNDERLAYMENT

Achieving the unique balance of structural strength with resilient sound dampening characteristics this is the ideal product for use with tile floor finishes. This 0.11" thick material is manufactured with 85% Recycled content has an antimicrobial treatment to prevent mold. For use beneath ceramic and porcelain tile flooring. Acoustiblok® 16 oz. with Acoustiwool-TF0.11 are Robinson Floor tested and rated "Residential" by the Tile Council of North America.



Order Number: TF0.11

Roll Size: 3' x 33.3' (100 Sq Ft)

ACOUSTIWOOL™ -WF0.125 WOOD FLOOR UNDERLAYMENT

The Acoustiwool-WF01.25 has been designed for use beneath hardwood, laminate and engineered wood floors. Used for wood floor finish installations *only*, on concrete or wood sub-floors beneath the Acoustiblok. Acoustiwool -WF0.125 works to decouple and isolate the top floor surface from the subfloor. The 1/8" thick wool composite is lightweight, flexible and easy to work with. Acoustiwool -WF0.125 is available with or without a moisture barrier laminated to it. Both have an antimicrobial treatment to prevent mold, extremely resilient, long lasting, and won't break down like air pockets in foam products.



Order Number: AW325
(without moisture barrier)

Roll Size: 6' x 325' (2,000 Sq Ft), 130 lbs.

Order Number: AW30MB
(with moisture barrier)

Roll Size: 3' x 33.3' (100 Sq Ft), 9 lbs.

ACOUSTIPAD™ CARPET FLOOR UNDERLAYMENT

Used floor installations (post-construction), after decking is down, between decking or concrete and Acoustiblok for carpet floor finishes. When used in addition to Acoustiblok, the Acoustipad works to decouple the Acoustiblok from the structural floor surface. The 3/8" thick foam pad is lightweight, flexible and easy to work with. Roll Size: 4' x 35' (140 SqFt.)



Order Number: AP435

171 FAST CURE MASTIC

Not a contact cement - It is waterproof and will bond Acoustiblok® to itself, wood, metal, and most other surfaces. Acoustiblok must be held in place while curing. Very fast cure time, varying with temperature and humidity. Due to the unique properties of Acoustiblok, most adhesives will not maintain a bond to the Acoustiblok, and the bond may release after a few days depending on the temperature. 28oz tube.



Order Number: FCA29

3M 5200 Marine Adhesive

Bonds Acoustiblok® to itself, wood, fiberglass, and most other surfaces. Complete curing time is approximately 7 days. 10oz tube.



Order Number: 3M5200MARADV

BOSTITCH PNEUMATIC CAP STAPLER KIT

The Bostitch SB150SLBC is a precision-built tool, designed for high speed, high volume fastening. Highly recommended for wood frame installations. Industrial quality with heavy-duty aluminum housing for a durable long life. Uses wide 5/16" crown SL staples that prevents puncture through the cap. Can be used for additional fastening applications of roofing felt, insulation and house wraps. Tool accepts 3/4" to 1-1/2" long SL series staples. Easy loading of caps and staples. Tool free depth of drive. Tool weight: 4.7 lb. Kit includes stapler, case, oil, wrench, 1000 caps, 1/4" air fitting, 1000 staples 1", and carrying case. NOTE: Put Bostitch staples & Bostitch caps approx every 8". Do not space further apart or within any overlap area as slight bending of the drywall surface may occur.



Order Number: BOSSTAP

REFILLS: CAP & STAPLES

BOSCAP - Bostitch SB Caps 1" Diameter, 1000 per pkg.

BOSSTAPLES - Bostitch SL5035 1" Staples, 5000 per pkg.